



## SportsPlay Equipment, Inc.

5642 Natural Bridge St. Louis, MO 63120 (314) 389-4140 (800) 727-8180 Fax (314) 389-9034  
www.sportsplayinc.com

### **541-916 COMPLETE BENT POST BACKSTOP WITH ACRYLIC RECTANGLE**

**Acrylic Rectangle-** shall be formed from 3/8" thick acrylic plastic with 1" x 2", gauge steel tubing reinforcing the edges and center. White border and target standard 5" x 5" goal mounting pattern.

**Rim** shall be constructed of two 5/8" diameter high strength steel rings welded together at a minimum of six places. Back and side plates shall be 3/16" thick and be continuously welded. The net attachment system shall be of a continuous wire formed netlock for nylon or chain. Rim shall have an orange powder coated finish.

**Pole** shall be constructed of 4 1/2" outside diameter RS40 zinc flow coated steel tubing with a 7 ga. wall thickness. Design shall be a bent gooseneck style and allow for a 48" bury into the ground and a 48" extension from the front of the pole to the face of the backboard and connect directly to the pole. Pole shall be designed to that the rim mounts directly to the horizontal pole section through the backboard to eliminate stress on the backboard during play.

Entire systems shall weigh approximately 261 lbs.